



# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/05/2015

Revision date: 03/21/2018

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Foam-safe Activator/Accelerator

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Heptane-based Activator/Accelerator (AH) - initiates and intensifies the chemical reaction of a SCA or CA.

Company  
Tech-Bond Solutions  
3774 Old Columbus Rd. NW, Suite 101  
Carroll, OH 43112  
877 565 7225 Fax: 866 411 0032

[www.tbonding.com](http://www.tbonding.com) [info@tech-bond.net](mailto:info@tech-bond.net)

#### 1.4. Emergency telephone number

Emergency number : 1 877 565 7225

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
STOT SE 3 H336  
STOT SE 3 H335  
Aquatic Chronic 2 H411

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS09

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P314 - Get medical advice and attention if you feel unwell  
P403+P235 - Store in a well-ventilated place. Keep cool

#### 2.3. Other hazards

Highly flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. In use, may form flammable / explosive vapour-air mixture.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Full text of H-phrases: see section 16

#### 3.2. Mixture

# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Hydrotreated light naphtha	(CAS No) 64742-49-0	>90%	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
N,N-dimethyl-p-toluidine	(CAS No) 99-97-8	<1%	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT RE 2, H373 Aquatic Chronic 3, H412

### SECTION 4: First aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.
First-aid measures after skin contact	: Rinse skin immediately with plenty of soap and water/shower for 10 minutes or longer. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: May cause slight irritation.
Symptoms/injuries after ingestion	: Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: No reactivity hazard other than the effects described in sub-sections below.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Protective clothing. Protective goggles. Safety glasses. Gloves.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
- Methods for cleaning up : Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Use only non-sparking tools and equipment in clean-up procedure.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No naked lights. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids. Oxidizing agents. Sources of ignition. Direct sunlight. Heat sources.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Naphtha (petroleum), hydrotreated light (64742-49-0)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm

### 8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective clothing. Protective goggles. Safety glasses.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing. Wear chemically resistant protective gloves.
- Respiratory protection : Wear appropriate mask. Wear respiratory protection.
- Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear, colorless liquid.
- Color : Clear
- Odor : Mild, aliphatic hydrocarbons.
- Relative evaporation rate (butylacetate=1) : 4.2
- Melting point : -101°C
- Boiling point : 94 - 98 °C
- Flash point : -4 °C
- Self ignition temperature : 254 °C
- Vapor pressure : 19 mm Hg @68°F
- Relative vapour density at 20 °C : 3.1
- Specific Gravity : 0.684 @ 77°F
- Solubility : Negligible.

# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits : 1.1 - 6.7 vol %

### 9.2. Other information

VOC content : 100 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Will not occur.

### 10.4. Conditions to avoid

Avoid high temperatures, direct sunlight, open flames, sparks, welding, smoking and other ignition sources. Avoid static charge accumulation and discharge.

### 10.5. Incompatible materials

Strong bases. Strong acids. Oxidizing agent. Sources of ignition. Direct sunlight. Heat sources.

### 10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Naphtha (petroleum), hydrotreated light (64742-49-0)

LD50 oral rat	> 15000 mg/kg
---------------	---------------

LD50 dermal rat	> 3000 mg/kg
-----------------	--------------

#### N,N-dimethyl-p-toluidine (99-97-8)

ATE CLP (oral)	100.000 mg/kg bodyweight
----------------	--------------------------

ATE CLP (dermal)	300.000 mg/kg bodyweight
------------------	--------------------------

ATE CLP (dust,mist)	0.500 mg/l/4h
---------------------	---------------

## SECTION 12: Ecological information

### 12.1. Toxicity

#### N,N-dimethyl-p-toluidine (99-97-8)

LC50 fishes 1	46 mg/l (96 h; Pimephales promelas; Lethal)
---------------	---

### 12.2. Persistence and degradability

#### Foam-safe Activator/Accelerator

Persistence and degradability	Biodegradable: Volatile
-------------------------------	-------------------------

#### N,N-dimethyl-p-toluidine (99-97-8)

Persistence and degradability	Biodegradable in water. Low potential for adsorption in soil.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### Foam-safe Activator/accelerator

Bioaccumulative potential	Not established
---------------------------	-----------------

#### N,N-dimethyl-p-toluidine (99-97-8)

BCF fish 1	33 (Pisces)
------------	-------------

Log Pow	1.729 (Experimental value; Equivalent or similar to OECD 107; 35 °C)
---------	--

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

### 12.4. Mobility in soil

Floats on water. Volatile. Readily absorbed into soil.

### 12.5. Other adverse effects

Other information : Avoid release to the environment. Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste disposal recommendations : After draining, leave to vent in a safe place away from sources of ignition and heat. Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. Dispose in a safe manner in accordance with local and national regulations
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment. RCRA hazardous waste. D001 (Ignitable). Incinerate waste in accordance with EPA and local regulations

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN3295 Hydrocarbons, liquid, n.o.s., 3, II
- UN-No.(DOT) : 3295
- DOT NA no. : UN3295
- DOT Proper Shipping Name : Hydrocarbons, liquid, n.o.s.
- Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquids



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

#### Additional information

- Other information : No supplementary information available.

#### ADR

- Transport document description : UN 3295, Packaging group II, class 3

#### Transport by sea

- Transport document description : UN 3295, Packaging group II, class 3

#### Air transport

- Transport document description : UN 3295, Packaging group II, class 3

# Foam-safe Activator/Accelerator

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Naphtha (petroleum), hydrotreated light (64742-49-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### N,N-dimethyl-p-toluidine (99-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

All components of this product are on the Canadian DSL list

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
STOT SE 3 H336  
STOT SE 3 H335  
Aquatic Chronic 2 H411

##### 15.2.2. National regulations

No additional information available

#### 15.3. US State regulations

No additional information available

### SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 4	Flammable liquids, Category 4
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Nothing herein shall be considered as recommending practices or products in violation of any patent, law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. WE MAKE NO WARRANTIES REGARDING THE PRODUCTS AND DISCLAIM ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.